

GBCS SCHEME



USN

--	--	--	--	--	--	--	--	--	--

15CV/CT51

Fifth Semester B.E. Degree Examination, Aug./Sept.2020 Design of RC Structural Elements

Time: 3 hrs.

Max. Marks: 80

*Note: 1. Answer any FIVE full questions, choosing ONE full question from each module.
2. Use of IS456-2000 and SP16 is permitted.*

Module-1

- 1 a. Explain balanced section, under reinforced section, and over reinforced section. (04 Marks)
- b. Obtain an expression for stress block parameter compressive force C_u and its position $\bar{y} = 0.42 x_u$ from top. (08 Marks)
- c. Obtain an expression for limiting percentage of steel and find limiting steel for M20 concrete and Fe415 steel. (04 Marks)

OR

- 2 a. Explain limit state of deflection and limit state of cracking. (04 Marks)
- b. What are the factors and which influence deflection? (04 Marks)
- c. Check the deflection requirement for the T beam continuous over 10m span having flange width 1200 mm web width 250mm and effective depth 400mm. Area of tension reinforcement 1500mm² area of compression reinforcement 960 mm². Adopt Fe415 steel. (08 Marks)

Module-2

- 3 a. A singly reinforced concrete beam 250 mm and 450mm deep up to centre of reinforcement is reinforced with 3-16mm dia effective cover 50mm, Effective span 6m. Determine central point load that can be applied in addition to self weight. Adopt M20 concrete and Fe500 steel. (08 Marks)
- b. Find the steel for a rectangular beam 300×700mm E.span 6m supporting a load of 80 kN/m. Adopt M20 concrete and Fe415 steel. (08 Marks)

OR

- 4 a. A doubly reinforced concrete beam having rectangular section 250mm × 500mm is reinforced with 2-12 mm dia in compression 4-20 mm dia in tension. Effective cover 40 mm, Effective span 5 m. Find M_u . Adopt M20 concrete and Fe415 steel. (08 Marks)
- b. A T beam having flange 1200 mm × 100mm web width 300 mm E.depth 550 mm, Area of tension steel 2280 mm². Find M_u . Adopt M20 concrete and Fe 500 steel. (08 Marks)

Module-3

- 5 Design a singly reinforced beam having effective span 7m to carry a live load of 20 kN/m for flexure and shear. Adopt M20 concrete and Fe415 steel. Also check the design for deflection and bond. (16 Marks)

OR

- 6 A hall 6m × 16m supported by beam spaced 4m c/c slab thickness 120mm. Supporting a live load 4 kN/m² and finishing 1 kN/m². Design interior T beam. Adopt M20 concrete and Fe415 steel. Assume bearing 500 mm. Overall depth limited to 450 mm. Take Effective cover 40mm. (16 Marks)



15CV/CT51

Module-4

- 7 Design a slab over a room $5.5\text{m} \times 4\text{m}$. Supporting a live load 4 kN/m^2 . Floor finishing 1.0 kN/m^2 . Design the slab if edges are restrained. Adopted M15 concrete and Fe415 steel. (16 Marks)

OR

- 8 The main stair of an office building has to be located in a stair case measuring $3.5\text{m} \times 5.5\text{m}$. Distance between the floor 3.75m . Design the stair. Live load 3 kN/m^2 . Adopt M20 concrete and Fe415 steel. (16 Marks)

Module-5

- 9 a. Design a column to support an ultimate load 1800 kN . Effective length of column 1.85m adopt M20 concrete Fe415 steel. (08 Marks)
b. A column $300 \times 500\text{ mm}$ supporting an ultimate load 1000 kN . $M_u = 25\text{ kNm}$. Find steel Adopt M20 concrete, Fe415 steel. Take cover 50mm . (08 Marks)

OR

- 10 Design a flat square footing to carry a column load 1000 kN column size $400 \times 400\text{mm}$ SBC of soil 100 kN/m^2 . Adopt M20 concrete, Fe415 steel. Show by calculation one way shear check, two way shear bond check and transfer of load at column base. (16 Marks)

* * * * *